



## EXCLUSIVE STANDARD FEATURES On Every Leer Walk-In



### Panel Gaskets

Foamed-in-place, flexible, vinyl gaskets assure vapor-tight panel joints, color matched to panels.



### Two-Piece Cam Action

Heavy-duty, offset cam fasteners provide maximum locking efficiency with versatility for easy disassembly.



### 4"-Thick Insulation

Class 1, rigid, foamed-in-place, non-CFC urethane with minimum density of 2.2 pounds per cubic foot.



### Standardized Panels

Various standard height panels are available to assure easy and accurate assembly.



### Tongue and Groove

Ensures precise, leak-proof fit of all walls, ceiling, floor and door panels.




### Vapor-Proof Light Fixture

With glass globe, lighted push-button switch and indoor/outdoor stainless steel switch cover.



### 26-Gauge Panel

Standard exterior and interior, ceiling and side panels are 26-gauge, embossed, galvanized steel.



### Chrome Latches

High-gloss finishes accent the heavy-duty, cam-lift hinges and lockable latch.



### Flush Metal Door

A variety of door sizes are available with in-fitting, flush mounting and panel finishes to match panel walls.



### Four Cam Locks Per Side - Standard

The most in the industry, providing positive seal of all joints and solid construction.



### 16-Gauge Stainless Steel Floor

Standard floor panels are designed to withstand uniformly distributed loads up to 700 pounds per square foot.